



Cut-out: Ø90mm-100mm

## FEATURES

- 3-CCT changeable.
- Compatible with leading and trailing edge phase cut dimmers.
- 3-year warranty.
- Aluminum & PC

## Technical Data

Input Voltage/Hz	AC200-240V 50/60Hz
Output Voltage/Current	DC80V/100mA
Power	10W
Rated Input Current	0.05A
PF value	>0.85
Ingress Protection	IP54
Operating Temperature	-10-40°C
Dimmability	Triac dimmable with <b>DIMMATE</b> driver

## Optical Data

LED Brand	Bridgelux SMD LED
CRI	Ra > 80
Colour temperature	3000K-4000K-5000K
System luminous efficacy up to	88lm/W

## Packaging

Box Dimensions	L115 x W115 x H95mm
Box Net Weight	0.265Kg
Box Gross Weight	0.315Kg
Carton Dimensions	L480 x W365 x H310 mm/36 PCS
Carton Net Weight	9.54Kg
Carton Gross Weight	12.14Kg



Model	CCT		Beam Angle	Lumen	Efficacy
PRO-DL4610	3000K	CRI 80+	100°	762lm	80lm/W
PRO-DL4610	4000K		100°	791lm	88lm/W
PRO-DL4610	5000K		100°	717lm	75lm/W