



Cut-out: Ø90mm-115mm

## FEATURES

- 3-CCT changeable.
- Compatible with leading and trailing edge phase cut dimmers.
- 3-year guarantee.

## Technical Data

|                        |                                           |
|------------------------|-------------------------------------------|
| Input Voltage/Hz       | AC200-240V 50/60Hz                        |
| Output Voltage/Current | DC80V/100mA                               |
| Power                  | 10W                                       |
| Rated Input Current    | 0.05A                                     |
| PF value               | >0.85                                     |
| Ingress Protection     | IP54                                      |
| Operating Temperature  | -10—40℃                                   |
| Dimmability            | Triac dimmable with <b>DIMMATE</b> driver |

## Optical Data

|                                |                   |
|--------------------------------|-------------------|
| LED Brand                      | Bridgelux SMD LED |
| CRI                            | Ra> 80            |
| Colour temperature             | 3000K-4000K-5000K |
| System luminous efficacy up to | 91lm/W            |

## Packaging

|                     |                              |
|---------------------|------------------------------|
| Box Dimensions      | L150 x W150 x H66mm          |
| Box Net Weight      | 0.331Kg                      |
| Box Gross Weight    | 0.4Kg                        |
| Carton Dimensions   | L620 x W470 x H225 mm/36 PCS |
| Carton Net Weight   | 9Kg                          |
| Carton Gross Weight | 13Kg                         |



| Model      | CCT   |            | Beam Angle | Lumen | Efficacy |
|------------|-------|------------|------------|-------|----------|
| PRO-DL4615 | 3000K | CRI<br>80+ | 100°       | 783lm | 82lm/W   |
| PRO-DL4615 | 4000K |            | 100°       | 813lm | 91lm/W   |
| PRO-DL4615 | 5000K |            | 100°       | 739lm | 78lm/W   |