



## FEATURES

- Low profile design suitable for low ceiling and IP65 waterproof ideal for bathroom area.
- CREE LED adopted, dim to warm available.
- Fit in most of MR16 LED downlight converter.
- Dimming capability. 1. Suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco; 2. DALI dimming.
- The driver with CE, RCM and SAA certification.

## Packaging

Box Dimensions	L145 x W145 x H50 mm
Box Net Weight	0.27Kg
Box Gross Weight	0.33Kg
Carton Dimensions	L450 x W302 x H275 mm/30 PCS
Carton Net Weight	5.7Kg
Carton Gross Weight	8.1Kg

**RoHS**



## Technical Specifications

Model	Power	Voltage	CRI	CCT	Beam Angle	Lumen	Efficacy	Dimmable	Colour
PRO-MD1010	9W	AC200-240V	80+	3000K	60°	810lm	89lm/W	Yes	Black

## Driver data Sheet

Brand	Dim Method	Model	Power	Input Voltage	Efficiency	Power Factor	Output Voltage	Output Current	THD
DIMMATE	Phase cutting	THA-09C0210-S	9W	AC200-240V	>82%	>0.9	33-38V	210mA	<25%

## Photometric Diagram

60°-3000K

